



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

DESCRIPTION

SIMULATION METHOD, PROGRAM, AND SYSTEM FOR CREATING A VIRTUAL THREE-DIMENSIONAL ILLUMINATED SCENE

TECHNICAL FIELD

The present invention is directed to a simulation method, a simulation program, and a simulation system for creating a virtual three-dimensional scene illuminated with one or more lighting fixture, and more particularly for realizing reproduction of dynamic image of the varying illuminated scene.

BACKGROUND ART

There have been proposed methods for simulating a three-dimensional illuminated scene with moving lighting fixtures. Typical methods are radiosity technique and laytrace technique both of which rely upon considerably complex arithmetic and therefore suffer from a delay in reproducing the illuminated scene, particularly with the use of a readily-available computing equipment. Because of this insufficiency, the above methods are practically limited to the reproduction of one still image of the illuminated scene, and are not well adapted for reproduction of dynamic image of the varying illuminated scene.

DISCLOSRE OF THE INVENTION

In view of the above problem, the present invention has been accomplished to provide a unique method, program, and system for simulating a virtual three-dimensional illuminated scene which is capable of rapidly reproducing the varying illuminated scene. The simulation method of the

present invention is provided to create the virtual three-dimensional scene illuminated at least one lighting fixture, and includes the steps of obtaining an object data with regard to a three-dimensional object to be illuminated with the lighting fixture, and specifying the lighting fixture and determining a position of the lighting fixture within a space of the three-dimensional object, in order to obtain output characteristic data as well as positional data of the lighting fixture. The object data is then transformed into an array of discrete elements to obtain object color component values inherent to each discrete element. The object color component values are assigned respectively to color components in a predetermined color space for designating the color of each discrete element. The object data is processed together with the output characteristic data and the positional data of the lighting fixture to obtain lamp color component values given to each of the discrete elements. The lamp component values are assigned respectively to the color components in the color space for designating the color of the lighting fixture illuminating each destined discrete element. Based upon the above processing, there are formed a plurality of lamp-by-element tables each being associated with each of the discrete elements, and storing the lamp color component values given to each corresponding one of the discrete elements. Then, the method goes to vary at least one of the output characteristic data and the positional data of the lighting fixture, and to re-calculate the lamp color component values given from the lighting fixture in order to obtain an updated color distribution. The updated color distribution is processed for rendering a view of the three-dimensional scene of the object.

The novel feature of the present invention resides in that the above

re-calculation includes the steps of determining the discrete elements to be illuminated by the lighting fixture varying its output characteristic data and/or its positional data, referring the lamp-by-element tables only associated with thus determined discrete elements and modifying the lamp color component values stored in the referred lamp-by-element tables as a function of the output characteristic data and the positional data being varied, and allocating the modified color component values to each of the corresponding discrete elements and combining the modified color component values to the object color component values of each discrete element, thereby realizing the updated color distribution over the entire array of the discrete elements.

Thus, the re-calculation of the lamp color component values can be only limited to the discrete elements being determined to be influenced by the change in the output characteristic and/or the position of the lighting fixture, which greatly reduces the calculation load and therefore enables to rapidly reproducing the lighting effect in prompt response to the varying output characteristic and/or the position of the lighting fixture. Accordingly, it is readily possible to simulate the continuously-changing illuminated scene of the object as a dynamic image.

In a preferred embodiment, two or more lighting fixtures are selected and specified with respect to the output-characteristic data as well as the positional data. In this instance, two or more the lighting fixtures are selected as variable components, and are varied in at least one of the output characteristic data and the positional data to determine the discrete elements to be illuminated by the lighting fixtures selected as the variable components. Then, reference is made to the lamp-by-element tables only associated with thus

determined discrete elements in order to modify the lamp color component values stored in the referred lamp-by-element tables. Thereafter, it is made to sum the lamp color component values in each of the referred lamp-by-element tables to give summed lamp color component values associated to each discrete element, and allocating the summed lamp color component values to the discrete elements, thereby realizing the updated color distribution over the array of the discrete elements.

The present invention also provides a simulation program for achieving the above method. The program is to be stored in a recordable medium for execution a computer and includes an input module which provides an input interface for entry of the object data with regard to the three-dimensional object to be illuminated with the lighting fixtures, a lamp setting module which provides a lamp setting interface for selecting one or more of the lighting fixtures and determining position of the selected lighting fixtures within the space of the three-dimensional object, and a lighting data processing module which gives output characteristic data and positional data of the selected lighting fixtures in response to the selection of the lighting fixture and the position thereof received at the lamp setting interface. An object processing module is included to transform the object data into an array of discrete elements, and to obtain object color component values inherent to each discrete element. Also a reference data generating module is included to calculate the object data, and the output characteristic data as well as the positional data of each of the selected lighting fixtures in order to obtain lamp color component values given to each of the discrete elements, and to provide a plurality of lamp-by-element tables each corresponding to each one of the

discrete elements and storing the lamp color component values. The lamp-by-element tables are located in a memory to be referred to thereafter. Further, the program includes a lighting control module which provides a lighting control interface for selecting at least one of the lighting fixtures and for selecting changes in at least one of the output characteristic data and the positional data of the lighting fixture. A re-calculation module is given to determine the discrete elements to be illuminated by the lighting fixture, and to refer to the lamp-by-element tables only associated with thus determined discrete elements. The re-calculation module modifies the lamp color component values stored in the referred lamp-element tables as a function of the output characteristic data and the positional data being varied. Also included in the program is a color allocating module which allocates the modified color component values to each corresponding one of the discrete elements and combines the modified color component values to the object color component values of each discrete element to thereby realize the updated color distribution over the entire array of the discrete elements. Further, an image producing module is included to process the updated color distribution for rendering the view of the three-dimensional illuminated scene of the object, and generating a image signal for presenting the view on a display.

The present invention further provides a simulation system for accomplishing the above method. The system is realized by a computer with an input device and the display, and includes an input interface for entry of an object data with regard to the three-dimensional object, a lamp setting interface for selecting one or more the lighting fixtures and for determining position of the selected lighting fixture, and a lighting data processing unit

which gives output characteristic data and positional data of the selected lighting fixture in response to the selection of the lighting fixture and the position thereof. An object processing unit is provided to transform the object data into an array of discrete elements, and to obtain object color component values inherent to each discrete element. Also included in the system is a reference data generating unit which calculates the object data, and the output characteristic data as well as the positional data of each of the selected lighting fixtures in order to obtain lamp color component values given to each of the discrete elements, and to provide a plurality of lamp-by-element tables each corresponding to each one of the discrete elements and storing the lamp color component values. The system includes a lighting control interface for selecting at least one of the lighting fixtures and for selecting changes in at least one of the output characteristic data and the positional data of the lighting fixture.

A re-calculation unit is included to determine the discrete elements to be illuminated by the lighting fixture, to refer to the lamp-by-element tables only associated with the determined discrete elements. Then, the re-calculation unit modifies the lamp color component values stored in the referred lamp-element tables as a function of the output characteristic data and the positional data being varied. Also included in the program is a color allocating unit which allocates the modified color component values to each corresponding one of the discrete elements and combines the modified color component values to the object color component values of each discrete element to thereby realize the updated color distribution over the entire array of the discrete elements. Further, an image producing unit is included to

process the updated color distribution for rendering the view of three-dimensional illuminated scene of the object, and generating the image signal for presenting the view on the display.

Preferably, the re-calculation unit includes a filter that retrieves the output characteristic data and the positional data of the lighting fixtures selected at the lamp setting interface, and determines which one or ones of the discrete elements are assigned to have the lamp color components values each of a sufficient level above a threshold, and defines thus determined discrete elements as active elements. Thus, the filter enables to refer to the lamp-by-element tables only associated with the active elements

The image producing unit is preferred to include a viewpoint selector which provides multiple viewpoints for the three-dimensional illuminated scene of the object, and selects anyone of the viewpoints in generating the image signal for presenting the view on the display. This feature can give enhanced preview capability for examining the lighting effect of the object.

Further, the image producing unit may be designed to produce the view of the three-dimensional illuminated scene of the object each time the re-calculating means operates to modify the lamp color component values, and to generate the image signals in succession for presenting the views as a movie.

In this connection, the system may include a raster memory that records the series of the image signals for replaying the movie for easy confirmation of the lighting effect.

The system may further include a fixture having a control output interface for connection with the actual lighting fixtures. The control output interface

processes the image signals recorded in the raster memory to generate a control signal for actuating the lighting fixtures in coincidence with the changes made for at least one of the output characteristic data and the positional data of the lighting fixtures. With this result, it is easy to control the actual lighting fixtures in exact harmony with the simulated lighting sequence.

Preferably, the system may include a lighting data input interface for receiving a control input which selects one or more of the lighting fixture, and describes a lighting schedule indicating a time-series of changes intended for at least one of the output characteristic data and the positional data of the selected lighting fixture. The lighting data input interface transmits the control input to the re-calculating unit for modifying the lamp color component values in accordance with the predetermined schedule of changes. With the inclusion of the light data input interface, it is easy to simulate and confirm the intended lighting schedule made at a dedicated lighting control board designed for controlling the lighting fixtures.

These and still other advantageous features of the present invention will be made apparent from the following description of the preferred embodiment of the present invention when taken in conjunction with the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a simulation system in accordance with a preferred embodiment of the present invention;

FIG. 2 is a block diagram illustrating a simulation program of the above embodiment;

FIG. 3 a flow chart illustrating the operation of the above system;

FIG. 4 is a perspective view of a three-dimensional object to be illuminated;
FIG. 5 is a chart illustrating the object divided into discrete elements and lamp-by-element tables assigned to each of the elements;
FIG. 6 is chart illustrating data structures of tables utilized in the above system;
FIGS. 7 and 8 are perspective view of the simulated scenes respectively with differently lighting conditions; and
FIG. 9 is a view illustrating a simulated image on a display of the above system.

BEST MODES FOR CARRYING OUT THE INVENTIONS

Referring now to FIG. 1, there is shown a simulation system in accordance with the present invention. The simulation system is made for creating a virtual three-dimensional scene illuminated with one or more lighting fixtures, and is adapted for, but not limited to, stage lighting with the use of multiple lighting fixtures. Although the illustrated embodiment explain the system with five (5) lighting fixtures or lamps **L001** to **L005** only for simplicity, the system should not interpreted to be limited to the number of the lighting fixtures. The system includes a computer **10** with an input device **12**, and a display **14**. The computer is programmed to give functional units and interfaces as illustrated in FIG. 1 for simulating the illuminated scene. An input interface **20** is included in the system to give object data describing a three-dimensional object **200**, i.e., a stage configuration to be illuminated, as shown in FIG. 4. For this purpose, the input interface **20** is arranged to have a drawing capability of creating the three-dimensional object **200** step-by-step using the input device **12**, i.e., keyboard and mouse. In addition, the input

interface **20** may be designed to accept an image file to translate its content into the three-dimensional object of a suitable format to be processed in the system.

An object processing unit **22** is included to transform the three-dimensional object **200** into an array of discrete elements, as shown in FIG. 5, and to obtain object color component values inherent to each discrete element. The object color component values denote intensities of individual color components, for example, R, G, and B components of a predetermined color space, and therefore are combined to specify the color of each discrete element. In the present embodiment, the object color component (R, G, B) value is set to be between zero (0) and (1), and a corresponding color is determined as a function of the individual color components (R, G, B). The object color component values for each discrete element are recorded together with coordinate of the element into an object-info table **32** that has a data structure shown in FIG. 6, and is loaded in a memory **30**.

The system includes a lamp setting interface **40** for specifying one or more of the lighting fixtures utilized for illuminating the object and the position thereof within a space of the three-dimensional object. For this purpose, the lamp setting interface **40** is designed for prompting a user to select the lighting fixture by its identification code or name from those of preset ones.

Associated with the lamp setting interface **40** is a lighting data processing unit **42** which fetches output characteristic data of the selected lighting fixture from an output characteristic data table **34** provided in the memory **30** and forward the data to a reference data generating unit **52** for further processing. The output characteristic data table **34** stores the lamp component (R, G, B) values

together with direction-dependent parameters for each of the lighting fixtures, as shown in FIG. 6. The direction-dependent parameters are defined, based upon the British Zonal Classification, to give a ratio (percentage) of the intensity (e.g., candela) of the light radiating to a particular point on the surface of a unit sphere from the center of the unit sphere where the lighting fixture is supposed to be located. The point on the surface of the unit sphere is represented by the latitude and longitude of the unit sphere. Thus, given the positional data of the lighting fixture within the space of the three-dimensional object, it is easy to calculate the lamp color component values of the light received at any point or element of the object from the selected lighting fixture. The calculation is made at the reference data generating unit 52 based upon the output of the lighting data processing unit 42. In short, the lighting data processing unit 42 fetches, from the lamp output characteristic data table 34, the output characteristic data of the selected lighting fixture, and passes the data together with the coordinates of each discrete element to the reference data generating unit 52.

Based upon the data from the unit 42, the reference data generating unit 52 calculates the lamp color component (R, G, B) values received at each discrete element of the object 200 from each of the selected lighting fixtures, and builds up a lamp-by-element table 36 for each of the discrete elements. Each of the lamp-by-element tables 36 lists the lamp color component (R, G, B) values of the individual lighting fixtures illuminating each corresponding discrete element, together with the summed component values, as shown in FIGS. 5 and 6. Each of the lamp color component values (C_p) is calculated by the following equation.

$$C_p = Lcd \cdot \cos \theta / r^2 \quad (1)$$

where Lcd is an intensity of the color component value in candela,
 $\cos \theta$ is an inner product of a normal to the element and a vector from the
 lighting fixture to the element, and

r is a distance between the lighting fixture and the discrete element.

The color component value may be referred to as a color component power
 or energy for representing the magnitude of the color component.

It is noted in this connection that the reference data generating unit **52**
 designates the lighting fixture that gives the lamp color component values any
 one of which is greater than a predetermined threshold, such that each of the
 lamp-by-element tables **36** lists the identification code of only thus designated
 lighting fixture together with the lamp color component values. For this
 purpose, the reference data generating unit **52** has a filter which compares the
 lamp color component values of the selected lighting fixture reaching the
 discrete element with the respective thresholds and ignore the lighting fixture
 as a non-influencing fixture when all of its lamp color values are less than the
 corresponding thresholds. When the lighting fixture is determined for the
 particular discrete element to give the lamp color component values all of
 which are less than the corresponding thresholds, the particular discrete
 element is judged not to be influenced or illuminated by the lighting fixture and
 is given the lamp-by-element table **36** of null record. In this manner, the
 lamp-by-element table **36** is created for each discrete element. Thus
 obtained lamp-by-element tables **36** are combined to give reference data that
 defines an initial illuminated condition of the object, i.e., a color distribution

over the entire array of the elements in combination with the object color component values stored in the object info table **32**, in the same fashion as will be discussed later with reference to a color allocation unit **72** and an image producing unit **80**.

A lighting control interface **60** is included in the system to receive an instruction selecting the lighting fixture and the associated changes in the output characteristic data and/or the position data. The lighting control interface **60** provides a form on the display **14** that prompts the user to enter the instruction through the keyboard and/or the mouse for specifying the lighting control intended by the user. A time-series of instructions are entered to give a lighting control schedule for changing the output characteristic data and/or positional data with respect to time for simulation of varying-lighting effect on the object. Such lighting control schedule may be recorded in a suitable format in an external recorder **90** and is transmitted therefrom as a control input through a lighting data input interface **62** to the lighting control interface **60**. The lighting control schedule may be given from a dedicated lighting control board **92** which is provided for actuating the lighting fixtures **L001** to **L005**.

Each time the instruction is given, a re-calculation unit **70** responds to fetch the output characteristic data and the positional data of the selected lighting fixture from the lamp output characteristic data table **34** and the object info table **32**, to determine which one or ones of the discrete elements are influenced by the selected lighting fixture. That is, the particular discrete element is determined to be influenced or illuminated by the selected lighting fixture when any one of the lamp color component values received at that

discrete element exceeds the corresponding threshold. Hereinafter, the particular discrete elements thus determined to be influenced by the particular lighting fixture are referred to simply as the active elements, and the lighting fixture assigned thereto is referred to simply as the influencing fixture, whenever it is deemed appropriate.

Then, the re-calculation unit **70** refers only to the lamp-by-element tables **36** associated with the active elements, and modifies the lamp color component values as a function of the output characteristic data and the positional data. The modification is made by using the above equation (1) for each of the color component (R, G, B) values. Thus, the re-calculation unit **70** refers the lamp-by-element tables **36** only associated with the active elements and make an arithmetic operation of modifying the color component values only related to the influencing fixture and gives the sum of each color component value of the individual active fixtures.

For instance, when the particular lighting fixture is controlled to move or change its projection angle, the re-calculation unit **70** firstly determines the active elements to be illuminated by the lighting fixture, i.e., the influencing fixture with reference to the object info table **32** and the lamp output characteristic data table **34**, and at the same time determines inactive elements which are no longer illuminated by this particular lighting fixture. Then, the re-calculation unit **70** refers to the lamp-by-element tables **36** only associated with the active elements in order to modify the lamp color component values in the record relating to the influencing fixture, and at the same time refers to the same tables **36** only associated with the inactive elements to modify or nullify the record relating to the influencing fixture.

When the particular lighting fixture is added, the re-calculation unit **70** determines the active elements to be illuminated by the lighting fixture, and refers to the lamp-by-element tables **36** only associated with the active elements in order to add the record in each of the tables **36** indicative of the identifying code of the influencing fixture together with the lamp color component values specific to each of the target elements. When the particular lighting fixture is deleted, the re-calculation unit **70** determines the inactive elements, and refers to the lamp-by-element tables **36** only associated with the inactive elements to thereby nullify the records in the tables relating to this lighting fixture. For the purpose of giving consistent and concise explanation of the essence of the present invention throughout the description and claims, the terms “modify” is used with reference to the color component values to encompass the usual meanings of “add” or “nullify”.

The sum of each color component value thus obtained for each of the lamp-by-element tables **36** is then fed to a color allocation unit **72** which refers to the object info table **32** and combines the sum with the object color component value for each corresponding one of the active element to give a color code indicating the color of the discrete element. For example, the color code is obtained by using the following known RGB function.

color code = RGB(exp1, exp2, exp3)

where exp1 is a red color component value multiplied by 255,

exp2 is a green color component value multiplied by 255, and

exp3 is a blue color component value multiplied by 255.

Then, the color allocation unit **72** gives an updated color distribution over the entire array of the discrete elements and transfers the same to an image

processing unit **80**. The image processing unit **80** includes an image rendering section **82** which processes the updated color distribution for rendering a view of three-dimensional illuminated scene of the object, and produces an image signal for representing the view on the display **14**. The rendering is made based upon a suitable three-dimensional modeling technique already known in the art, and is not explained in detail. Included in the image processing unit **80** is a viewpoint selecting interface **84** for selecting one of various viewpoints and instructing the image rendering section **82** to give the image of the illuminated object from the selected viewpoint. The image signal of the view is continuously updated in accordance with the lighting control schedule to give a succession of the view, i.e., a dynamic image of the view on the display **14**. At the same time, the image signal is accumulated as in a raster memory **86** to enable a playback function. Further, the system includes a control output interface **88** for connection with the external recorder **90** to record the image signal, and also with the lighting control board **92** in order to actuate the real lighting fixtures **L001** to **L005** in an exact manner as the simulation result.

FIG. 2 shows the structure of a program for achieving the above simulation. The program is written in one of state-of-art programming languages and is stored in a recordable medium such as a CD-ROM or the disk to be installed into and executed at the computer. The program is composed of various modules implementing the specific tasks as mentioned with reference to the system of FIG. 1. An input module **120** is provided to create the input interface **20** on the display **14** for prompting the user to enter the object data describing the three-dimensional object **200**, as shown in FIG.

4. An object processing module **122** is provided to realize the object processing unit **22** for processing the object to create the object info table **32**. A lamp setting module **140** is provided to create the lamp setting interface **40**, while a lighting data processing module **142** realizes the lighting processing unit **42** which gathers the output characteristic data and the positional data of the selected lighting fixture from the lamp output characteristic data table **34** provided in the memory **30**, in addition to the coordinates of the discrete elements from the object info table **32**. A reference data generating module **152** is provided to realize the reference data generating unit **52** for building up the lamp-by-element tables **36**. A lighting control module **160** provides the lighting control interface **60** which prompts the user to set the lighting control schedule for simulating the effect of illuminating the object. A re-calculation module **170** realizes the re-calculation unit **70** to modify the lamp color component values for the active elements with respect to the influencing fixture and to sum the lamp color component values from all of the influencing fixtures. A color allocation module **172** realizes the color allocation unit **72** to obtain the updated color distribution which is processed at an image rendering module **182** which realizes the image rendering section **82** to produce the image signal. A viewpoint selecting module **184** is also included to create the viewpoint selecting interface **84** for giving the view of the resulting illuminated object from the selected viewpoint.

The operation of the above system and program will be explained again in brief with reference to a flow chart of FIG. 3. After the object data entry and lamp setting are completed (steps 1 and 2), the object processing and the lighting data processing are made to obtain information about the coordinates

of the discrete elements of the object together with the output characteristic data and positional data of the selected lighting fixture (steps 3 and 4). Then, the reference data processing is made to allocate the lamp color component values to each discrete element, building up the lamp-by-element tables **36** with respect to each of the discrete elements, as shown in FIG. 5, and combining the lamp color component values with the object color component values to realize the reference or initial view of the illuminated scene, as shown in FIG. 7. The initial view is then continuously updated, as shown in FIG. 8, to give the simulated dynamic image by repeating a loop of making the lighting control, the re-calculation of the lamp color component values, the color allocation, and the image processing (steps 6 to 9). By comparison between the views of FIGS. 7 and 8, the changing illumination effect is appreciated by the changing brightness of the portions of the object, although the actual image is represented in colors.

The system of the present invention further includes an envelop drawer **85** which determines a projection cone of the light beam emanating from each of the selected lighting fixture by referring to the output characteristic data and the positional data of the lighting fixture, in addition to the coordinates of the active elements, and draws the envelop **208** of the projection cone, either by lines or shades for adding visual emphasis on the illumination effect of the object **200**, as shown in FIG. 9. The envelop drawer **85** is also realized by a corresponding module of the program and gives a user interface **108** by which the user can selectively add the emphasis for each of the individual lighting fixtures.

CLAIMS

1. A simulation method for creating a virtual three-dimensional scene illuminated with at least one lighting fixture, said method comprising the steps of:
- a) obtaining an object data with regard to a three-dimensional object to be illuminated with said lighting fixture;
 - b) specifying said lighting fixture and determining a position of said lighting fixture within a space of said three-dimensional object, in order to obtain output characteristic data as well as positional data of said lighting fixture;
 - c) transforming said object data into an array of discrete elements and obtaining object color component values inherent to each discrete element, said object color component values being assigned to respective color components in a predetermined color space for designating the color of each discrete element;
 - d) processing said object data, and said output characteristic data as well as said positional data of said lighting fixture in order to obtain lamp color component values given to each of said discrete elements, said lamp component values being assigned to the respective color components in said color space for designating the color of said lighting fixture illuminating each destined one of the discrete elements,
 - e) providing a plurality of lamp-by-element tables each associated with each of said discrete elements, each of said lamp-by-element table storing the lamp color component values;
 - f) varying at least one of said output characteristic data and said positional

data of said lighting fixture;

- g) determining the discrete elements to be illuminated by said lighting fixture;
- h) referring to said lamp-by-element tables only associated with thus determined discrete elements and modifying the lamp color component value stored in the referred lamp-by-element tables as a function of said output characteristic data and said positional data being varied;
- i) allocating said modified color component values to each of the corresponding discrete elements and combining the modified color component values to said object color component values of each discrete element to realize an updated color distribution over the entire array of said discrete elements; and
- j) processing said updated color distribution for rendering a view of three-dimensional illuminated scene of said object.

2. A simulation method as set forth in claim 1, wherein two or more lighting fixtures are selected and specified with respect to said output-characteristic data as well as said positional data, said method including the steps of

- i. selecting two or more said lighting fixtures as variable components, and varying at least one of said output characteristic data and said positional data of said lighting fixtures to determine the discrete elements to be illuminated by said lighting fixtures selected as the variable components;
- ii. referring to said lamp-by-element tables only associated with thus determined discrete elements and modifying the lamp color component

values stored in the referred lamp-by-element tables for said lighting fixtures;

- iii. summing the lamp color component values in each of the referred lamp-by-element table to give summed lamp color component values associated with each said discrete element, and allocating the summed lamp color component values to said discrete elements, thereby realizing the updated color distribution over the array of the discrete elements.

3. A simulation program for creating a virtual three-dimensional scene illuminated with multiple lighting fixtures, said program being adapted to be stored in a recordable medium for execution at a computer and comprising:

- a) an input module which provides an input interface for entry of an object data with regard to a three-dimensional object to be illuminated with said lighting fixtures;
- b) a lamp setting module which provides a lamp setting interface for selecting one or more said lighting fixtures and determining position of said selected lighting fixtures within a space of said three-dimensional object,
- c) a lighting data processing module which gives output characteristic data and positional data of said selected lighting fixtures in response to the selection of said lighting fixture and the position thereof received at said lamp setting interface;
- d) an object processing module which transforming said object data into an array of discrete elements, and which obtains object color component values inherent to each discrete element, said object color component

- values being assigned to respective color components in a predetermined color space for designating the color of each discrete element;
- e) a reference data generating module which calculates said object data, and said output characteristic data as well as said positional data of each of said selected lighting fixtures in order to obtain lamp color component values given to each of said discrete elements, said lamp component values being assigned to the respective color components in said color space for designating the color of said lighting fixture illuminating each destined one of the discrete elements, said reference data generating module providing a plurality of lamp-by-element tables each corresponding to each one of said discrete elements and storing the lamp color component values;
 - f) a lighting control module which provides a lighting control interface for selecting at least one of said lighting fixtures and selecting changes in at least one of said output characteristic data and said positional data of the lighting fixture;;
 - g) a re-calculation module which determines the discrete elements to be illuminated by said at least one lighting fixture, and refers to said lamp-by-element tables only associated with thus determined discrete elements, said re-calculation module modifying the lamp color component values stored in the referred lamp-element tables as a function of said output characteristic data and said positional data being varied;
 - h) a color allocating module which allocates said modified color component values to each corresponding one of said discrete elements and combines the modified color component values to said object color component

values of each discrete element to thereby realize a an updated color distribution over the entire array of said discrete elements,

- i) an image producing module which processes said updated color distribution for rendering a view of three-dimensional illuminated scene of said object, and generating an image signal for presenting said view on a display.

4. A simulation system for creating a virtual three-dimensional scene illuminated with one or more lighting fixtures, said system comprising:

- a) an input interface for entry of an object data with regard to a three-dimensional object to be illuminated with said lighting fixtures;
- b) a lamp setting interface for selecting one or more said lighting fixtures and for determining position of said selected lighting fixtures within a space of said three-dimensional object,
- c) a lighting data processing unit which gives output characteristic data and positional data of said selected lighting fixtures in response to the selection of said lighting fixture and the position thereof received at said lamp setting interface;
- d) an object processing unit which transforms said object data into an array of discrete elements, and which obtains object color component values inherent to each discrete element, said object color component values being assigned to respective color components in a predetermined color space for designating the color of each discrete element;
- e) a reference data generating unit which calculates said object data, and

said output characteristic data as well as said positional data of each of said selected lighting fixtures in order to obtain lamp color component values given to each of said discrete elements, said lamp component values being assigned to the respective color components in said color space for designating the color of said lighting fixture illuminating each destined one of the destined discrete elements,

- f) a memory providing a plurality of lamp-by-element tables each corresponding to each one of said discrete elements and storing the lamp color component values;
- g) a lighting control interface for selecting at least one of said lighting fixtures and selecting changes in at least one of said output characteristic data and said positional data of the lighting fixture;
- h) a re-calculation unit which determines the discrete elements to be illuminated by said at least one lighting fixture, and refers to said *lamp-by-element tables only associated with thus determined discrete elements*, said re-calculation unit modifying the lamp color component values stored in the referred lamp-element tables as a function of said output characteristic data and said positional data being varied;
- i) a color allocating unit which allocates said modified color component values to each corresponding one of said discrete elements and combines the modified color component values to said object color component values of each discrete element to thereby realize a an updated color distribution over the entire array of said discrete elements, and
- j) an image producing unit which processes said updated color distribution for rendering a view of three-dimensional illuminated scene of said object,

and generating an image signal for presenting said view on a display.

5. The system as set forth in claim 4, wherein
said re-calculation unit includes a filter that retrieves the output characteristic data and said positional data of the lighting fixtures selected at said lamp setting interface, and determines which one or ones of said discrete elements are assigned to have the lamp color components values each of a sufficient level above a threshold, and defining thus determined discrete elements as active elements, said filter enabling said re-calculation unit to refer to said lamp-by-element tables only associated with the active elements.

6. The system as set forth in claim 4, wherein
said image producing unit includes a viewpoint selector which provides multiple viewpoints for said three-dimensional illuminated scene of said object, and selects anyone of said viewpoints in generating said image signal for presenting said view on the display.


7. The system as set forth in claim 4, wherein
said image producing unit produces the view of the three-dimensional illuminated scene of said object each time said re-calculating means operates to modify the lamp color component values, and generates the image signals in succession for presenting said views as a movie.


8. The system as set forth in claim 6, further including a raster memory that records the series of said image signals for replaying said movie.

9. The system as set forth in claim 8, further including a control output interface for connection with the actual lighting fixtures, said control output interface processing said image signals recorded in said raster memory to generate a control signal for actuating the lighting fixtures in coincidence with the changes made for at least one of said output characteristic data and said positional data of said lighting fixtures selected at said lighting control interface.

10. The system as set forth in claim 4, further including a lighting data input interface for receiving a control input which selects one or more of said lighting fixture, and describes a lighting schedule indicating a time-series of changes intended for at least one of said output characteristic data and said positional data of the selected lighting fixture, said data input interface transmitting said control input to said re-calculating unit for modifying the lamp color component values in accordance with the lighting schedule.

FIG. 1





3/8

FIG. 3




FIG. 4




FIG. 5




FIG. 6

32

OBJECT INFO TABLE				
ELEMENT	R	G	B	COORDINATES
000001	0.044	0.052	0.086	0001, 0001
000002	0.024	0.072	0.034	...
				...
				...
010011	0.021	0.014	0.025	...

34

LAMP OUTPUT CHARACTERISTIC DATA TABLE								
LAMP	R	G	B	S(0,0)	S(0,10)	S(0,20)	...	S(90,180)
001	0.745	0.549	0.086	80	75	68	...	20
002	0.227	0.072	0.752	58	42	35	...	30
...	
099	0.862	0.392	0.196	74	69	62		41

36

LAMP-BY-ELEMENT TABLE			
LAMP	R	G	B
001	0.745	0.549	0.086
002	0.227	0.072	0.752
...			
SUM	0.972	0.621	0.838

7/8

FIG. 7




FIG. 8





FIG. 9



INTERNATIONAL SEARCH REPORT

International Application No
PCT/JP2004/004234

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H05B37/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 495 305 A (VARI LITE INC) 22 July 1992 (1992-07-22) page 3, line 48 - page 24, line 14; figures 1-20	1-10
Y	US 5 867 166 A (SCHICK RUSSELL ET AL) 2 February 1999 (1999-02-02) column 4, line 36 - column 18, line 11; figures 1-6	1-10
A	"Martin ShowDesigner (MSD 4.2)" September 2000 (2000-09), MARTIN PROFESSIONAL A/S, AARHUS, DENMARK, XP002287388	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

7 July 2004

Date of mailing of the international search report

17/08/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Albertsson, E

INTERNATIONAL SEARCH REPORT

International Application No
PCT/JP2004/004234

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	AUTODESK WHITE PAPER: "Lightscape 3.2: Concepts and Techniques in Computer Generated Lighting Simulation" 2001, AUTODESK INC , SAN RAFAEL, CA, USA , XP002287389 -----	
A	WO 03/015477 A (KRAUSE CHRISTIAN ; MARTIN PROFESSIONAL AS (DK)) 20 February 2003 (2003-02-20) -----	
A	WO 02/101702 A (COLOR KINETICS INC) 19 December 2002 (2002-12-19) -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/JP2004/004234

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0495305	A	22-07-1992	US 5307295 A	26-04-1994
			AT 182701 T	15-08-1999
			AU 652409 B2	25-08-1994
			AU 1008592 A	16-07-1992
			CA 2057268 A1	15-07-1992
			DE 69131478 D1	02-09-1999
			DE 69131478 T2	20-01-2000
			DK 495305 T3	29-11-1999
			EP 0495305 A2	22-07-1992
			JP 6096603 A	08-04-1994
			KR 157328 B1	16-11-1998
US 5867166	A	02-02-1999	AU 6766096 A	05-03-1997
			CA 2229027 A1	20-02-1997
			EP 1434171 A2	30-06-2004
			EP 1434172 A2	30-06-2004
			EP 0850462 A2	01-07-1998
			JP 11511277 T	28-09-1999
			JP 2004102998 A	02-04-2004
			JP 2004046886 A	12-02-2004
			WO 9706512 A2	20-02-1997
			US 6064393 A	16-05-2000
			US 6016150 A	18-01-2000
			US 6252608 B1	26-06-2001
			US 6326964 B1	04-12-2001
			US 6292194 B1	18-09-2001
			US 5977977 A	02-11-1999
			US 5880737 A	09-03-1999
			US 5808617 A	15-09-1998
			US 5864342 A	26-01-1999
			US 5852443 A	22-12-1998
			US 5870097 A	09-02-1999
			US 5886701 A	23-03-1999
			US 5999189 A	07-12-1999
			US 6005582 A	21-12-1999
			US 5990904 A	23-11-1999
			US 5949428 A	07-09-1999
			US 6008820 A	28-12-1999
WO 03015477	A	20-02-2003	WO 03015477 A1	20-02-2003
			EP 1413176 A1	28-04-2004
WO 02101702	A	19-12-2002	US 2002057061 A1	16-05-2002
			EP 1337784 A2	27-08-2003
			WO 02061330 A2	08-08-2002
			WO 02101702 A2	19-12-2002
			US 2002171365 A1	21-11-2002
			US 2002171377 A1	21-11-2002
			US 2002163316 A1	07-11-2002
			US 2002153851 A1	24-10-2002
			US 2002130627 A1	19-09-2002
			US 2002171378 A1	21-11-2002
			US 2003057887 A1	27-03-2003
			US 2004052076 A1	18-03-2004
			EP 1393599 A2	03-03-2004
			EP 1395975 A2	10-03-2004
			WO 02098182 A2	05-12-2002
			WO 02099780 A2	12-12-2002

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/JP2004/004234

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 02101702	A	US 2003057886 A1	27-03-2003
		US 2003057890 A1	27-03-2003
		US 2003137258 A1	24-07-2003
		US 2003222587 A1	04-12-2003
		US 2004090191 A1	13-05-2004
		EP 1428415 A1	16-06-2004
		WO 03026358 A1	27-03-2003
<hr/>			